



Fixture Type: \_\_\_\_\_  
 Client: \_\_\_\_\_  
 Project: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Catalog#: \_\_\_\_\_



Model	Size (inches) & Weight (lbs)			
	L (in)	W (in)	H (in)	Weight
CM-101-1	11.81	11.81	3.54	1.66
CM-101-2	13.78	13.78	3.54	2.21
CM-101-3	15.75	15.75	3.54	3.10

MODEL	NOMINAL LUMEN OUTPUT	KELVIN (SELECTABLE)	
CM-101-1	12L = 1200 lm	5CCT	2700/ 3000/ 3500/ 4000/ 5000K
CM-101-2	14L = 1800 lm		
CM-101-3	20L = 2000 lm		

## Specifications

### Housing

- Brushed Nickel steel, white housing.

### Electrical

- Universal 120V AC voltage (60Hz) is standard.
- Triac dimming.
- Input transient surge protection = 0.5kV.
- Power factor > 0.90.

### Optical System

- Polycarbonate diffuser.
- Field selectable 2700k(soft white), 3000k(warm white), 3500k(warm/neutral white), 4000k (neutral white) and 5000k (cool white) color temperatures\*.
- Delivers a range of 1,200 to 2,000 nominal lumens\*.
- Long-life LEDs provide 139,000 hours of operation with at least 70% of initial lumen output (L70)\*\*.
- LED color maintenance < -0.00346 chromaticity shift ( $\Delta u'v'$ ) over the initial 6,000 hours of operation.
- Color rendering index > 90.

### Mounting

- Surface mounting and retrofit installation.
- Covered ceiling mount .

### Code Compliance

- cETLus listed for damp locations .
- Complies with FCC part 15, class B.

### Warranty

- 5-year warranty on all electronics and housing.

\* Default color temperature 4000K and highest lumen output.

\*\*L70 hours are IES TM-21-11 calculated hours.



Fixture Type: \_\_\_\_\_  
 Client: \_\_\_\_\_  
 Project: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Catalog#: \_\_\_\_\_

## Compatible Dimmers & Controls

Manufacturer	Model Number		
<b>Lutron</b>	TG-600PR-WH	SLV-600P-AL	DVCL-153P
	S-600PR-WH	DV-600PR-WH	MSCL-OP153M
	CTCL-153PDH-WH	SCL-153PH-WH	PD-6WCL
	TGCL-153PH-LA	GT-600P	MACL-153M//MA-R
<b>Leviton</b>	6672	6674	IPL06
	RNL06	DSL06	-

## Dimensional Drawing

