



Fixture Type: _____
 Client: _____
 Project: _____
 Location: _____
 Catalog#: _____



FEATURES

USE OF PRODUCT

The intended use of this product is for recreational areas, streets, parking lots, and pedestrian walkways.

FINISH

Matt-finished, thermoset polyester oven baked powdercoat finish. Available in standard dark polyester bronze or consult factory for made to order architectural finishes.

MOUNTING

Available in Slip-over or Pole bracket in round or square. Fixture pole must be mounted on a concrete base (supplied by others).

NOTES

Poles available according to mounting configuration.

EPA

Effective Projected Area (Sq. Ft.):

Type A: 2.589 ft² (1 fixture),
Type B: 2.952 ft² (1 fixture)

LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 3000K, 3500K, 4000K, or 5000K with CRI>83. LEDs placed on high performance aluminum heatsink for reduced junction temperatures and extended life.

LISTINGS/COMPLIANCE

- CEC Compliant emergency driver
- CSA - Suitable for wet locations.
- Dark Sky Compliant

HOUSING

Heavy-duty spun and cast aluminum housing with arm constructed of rugged aluminum.

OPTICS

Clear tempered glass available with distribution types. Lens is sealed by a one-piece silicone gasket which prohibits entrance of outside contaminants.

DRIVER

Durable LED driver operates at 120-277V with 0-10V dimming protocol. Power factor: 0.90; 50 to 60 Hz. Driver protections includes: Output open load, over-current and short-circuit, and over-temperature with auto recovery. -30°C Min Temp. to 40°C Max Temp. Step down transformer may be utilized for 480V or 347V applications.

ORDERING INFO

SERIES	SIZE	WATT/LUMENS	VOLTAGE	COLOR TEMPERATURE	DISTRIBUTION TYPES	MOUNTING	ARM DETAILS
AL-101	A- 24.50"	35 - 35W/2002lm 50 - 50W/2085m	UNV- 120V-277V	35 - 3500K 40 - 4000K 50 - 5000K	T5- Type V	RPB3 - Round Pole 3" Bracket RPB4 - Round Pole 4" Bracket RPB5 - Round Pole 5" Bracket SPB3 - Square Pole 3" Bracket SPB4 - Square Pole 4" Bracket SPB5 - Square Pole 5" Bracket RSP3 - 3" Round Slip-over Pole RSP4 - 4" Round Slip-over Pole RSP5 - 5" Round Slip-over Pole CX- Custom Mounting	S- Straight C- Curved CX- Custom Arm
	B- 30.00"	50 - 50W/2085lm					

FINISH

OPTIONS

BZ² - Bronze
 MTO³ - Made to order
 MGT³ - Marine grade made to order
 PC - Photocell 120-277V
 MS - Motion Sensor (Bi-Level)
 EM - Emergency battery
 SP10 - Surge Protection 10KV

Notes

1. Step-down transformer required
2. Standard finish.
3. RAL number required.