



Fixture Type: _____
 Client: _____
 Project: _____
 Location: _____
 Catalog#: _____



FEATURES

USE OF PRODUCT

The intended use of this product is for parking lots, walkways, shopping centers, recreational areas, or any open outdoor commercial or industrial space.

MOUNTING

Fixture pole must be mounted on a concrete base (supplied by others).

FINISH

Thermoset polyester oven-baked powdercoat, in any standard color. Made to order finishes are available to your specification.

LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 3000K, 3500K, 4000K, or 5000K with CRI>83. LEDs placed on high performance aluminum heatsink for reduced junction temperatures and extended life.

EPA

Effective Projected Area (Sq. Ft.):
 Type A: 1.950 ft² (1 fixture),
 Type B: 2.750 ft² (1 fixture)

HOUSING

Housing fabricated from one-piece spun aluminum .08" thick with continuous heliarc welded at all seams. It features stainless steel external hardware. Available in standard decorative reveal upon request. All model feature a .125" ballast plate and a .250" reinforcing plate for arm attachment.

- The doorframe is spun from heavy duty aluminum and is secured by two stainless steel captive screws for easy maintenance.
- Door opens on heavy duty radius hinges.

OPTICS

Segmented reflector with specular aluminum finish.

LISTINGS/COMPLIANCE

- CEC Compliant emergency driver
- CSA - Suitable for wet locations.
- Dark Sky Compliant

DRIVER

Durable LED driver operates at 120-277V with 0-10V dimming protocol. Power factor: 0.90; 50 to 60 Hz. Driver protections includes: Output open load, over-current and short-circuit, and over-temperature with auto recovery. -30°C Min Temp. 40°C Max Temp. Step down transformer may be utilized for 480V or 347V applications. Optional 10kA surge protector (120-277V).

SERIES	HEIGHT	WATT/LUMENS	VOLTAGE	COLOR TEMPERATURE	DISTRIBUTION TYPES	LENS	MOUNTING
T391LED	A- 20"	35 - 35W/2002lm 50 - 50W/2085lm	UNV - 120V-277V	35 - 3500K 50 - 5000K	T5 - Type V	F - Flat	AM6S- 6" Arm Mount Square AM10S- 10" Arm Mount Square AM6R- 6" Arm Mount Round AM10R- 10" Arm Mount Round made to order
	B- 22"	50 - 50W/2085lm					

FINISH

BZ¹ - Bronze
 MT⁵ - Made to order
 MGT⁵ - Marine grade

OPTIONS

PC- Photocell 120-277V
 MS- Motion Sensor (Bi-Level)
 EM- Emergency battery
 SP10- Surge Protection 10KV
 HSS- House side shield

Notes

1. Available in size A.
2. Available in size B.
3. Standard distribution types.
4. Standard finish.
5. RAL number required.