



Fixture Type: _____
 Client: _____
 Project: _____
 Location: _____
 Catalog#: _____

DIMENSION



Diameter (D): 4 1/4" (120mm)
 Height (A): 34" (865mm)

PL-103

PRODUCT INFORMATION

Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Flat Top. Bollards Can Be Cut to Custom Lengths Upon Request.

Driver:

Electronic Driver, 120-277V, 50/60Hz; Less Than 200/0 THD and PF>0.90. Standard Internal Surge Protection 2kV. 0-10V Dimming Standard for a Dimming Range of 100% to 10%; Dimming Source Current is 150 Microamps.
 12V: Electronic Driver, 12-17VAC Input, 50/60Hz, Non-Dimmable

Lens:

Clear Polycarbonate Vandal-Resistant Lens

Mounting:

Mounting Kit with 8" Anchor Bolts, Included.

EasyLED:

Aluminum Boards

Wattage:

3600 17w Array: 16.6w, System: 18.9w
 1800 & 1200 16w Array: 15.5w, System: 18.5w; (70w HID Equivalent)

Ratings:

CSA: Listed for Wet Locations, ANSI/UL 1598, 8750 IP66 Sealed LED Compartment

Ordering Example: 6910-C-3-U-BL-C-BZ-SF-SF

ORDERING INFORMATION

Model	Driver	CCT	Lens	Color	Height	Options
6910-360 - Full Cutoff Bollard 360°	U - 120/277V V - 12V	3K - 3000K 4K - 4000K 5K - 5000K	Clear Polycarbonate Vandal-Resistant Lens	Z - Bronze B - Black C - Custom	(Leave Blank) - 34" Standard Height 30 - 30"	SF - Single Fuse DF - Double Fuse SP - Surge Protection GFI - GFCI Outlet, 15A, 120V
6910-120 - Full Cutoff Bollard with 120° Shield						
6910-180 - Full Cutoff Bollard with 180° Shield						